

SC Fastening Systems, LLC.

Your Single Source Supplier for OEM Hardware and Industrial Supplies

Please print this page, fill in as much information as possible and fax it to 440.232.9765. In order to provide the most economical solution between stock, non stock and custom springs please fill in the approximate annual requirement.

Company				Contact				
Address								
Phone No.				Fax No.				
Annual Quantity								
Type number (1 to 8)			Number of springs per lid	1.		2.		
Weight of lid (W)			lb	Opening angle. (o)				degrees
Distance from pivot end of lid (L)								inches.
Distance from pivot to center of gravity (C)								inches.
Maximum depth of mounting position (G)								inches.
(If no value is stated optimum value will be used)								
Thickness of lid.								inches.
Do you wish the lid to open automatically or to remain closed under its own weight								
Remain closed.				Open automatically. (lid will need catch)				
Do you wish the spring to be mounted ..				Inside		Outside		
Ambient operating temp. °F				TYPE 7 ONLY				
Anticipated N ^o . of cycles per minute				Distance of C.O.G below the pivot (B)				inches
Center of gravity distances can normally be estimated				Distance of end of lid below the pivot (D)				inches
<p>1, 90° OPENING</p>		<p>2, RESTRICTED OPENING</p>		<p>3, BEYOND 90° OPENING</p>		<p>4, ABOVE HORIZONTAL OPENING</p>		
<p>5, 180° OPENING</p>		<p>6, BELOW HORIZONTAL OPENING</p>		<p>7, BELOW TO ABOVE HORIZONTAL OPENING</p>		<p>8, OTHER (PLEASE SPECIFY)</p>		

7733 First Place • Unit 2 • Oakwood Village, Ohio 44146
 800/232-2659 • fax: 440/232-9765 • www.scfastening.com